5

Applicant:

Armand Cote

For:

Breakaway Utility Pole

1. A breakaway utility pole for placement in the ground, comprising:

a first elongated pole portion in the ground and partially protruding therefrom;

a second elongated pole portion interfitted into said first portion above

the ground; and

means for hanging utility wires from said utility pole.

2. The breakaway utility pole of claim 1 in which said first and second portions are made of plastic.

3. The breakaway utility pole of claim 2 in which said second portion is substantially hollow.

The breakaway utility pole of claim 3 in which said second portion is generally annular in cross-section.

The breakaway utility pole of claim 1 in which said first portion includes at its upper end one part of a two-part male/female connector element.

The breakaway utility pole of claim 5 in which said second portion includes at its lower end the second part of said male/female connector element.

The breakaway utility pole of claim of in which said second portion further includes at its upper end one part of another two-part male/female

8

5

Applicant:

Armand Cote

For:

Breakaway Utility Pole

connector element.

8. The breakaway utility pole of claim 7 further including a third pole portion having the second part of said another two-part male/female connector element.

- 9. The breakaway utility pole of claim 1 in which said means for hanging wires includes a third pole portion interfitted into said second pole portion at the upper end thereof.
- 10. The breakaway utility pole of claim 9 in which said first and third pole portions are substantially solid.

The breakaway utility pole of claim 9 in which said first, second and third pole portions are generally cylindrical.

The breakaway utility pole of claim It further including a pointed member into which said first pole-portion fits.

g

5





Applicant:

Armand Cote

For:

Breakaway Utility Pole

Sub a3 13. A breakaway utility/pole, comprising:

a lower member embedded in the ground;

an intermediate generally cylindrical member interfitted into said lower member and protruding up; and

a top member interfitted into said intermediate member, and carrying utility wires;

wherein said intermediate member is a hollow plastic tube which

fractures upon a relatively fow impact from an automobile.

The breakaway utility pole of claim 12 in which said intermediate member is fluted along its length to weaken it so that it fractures more easily.